




宗申动力
ZONG SHEN POWER

Model: NH130
BOM No: 1TZZQGN07
NH100
NH100
V01
2018-12-26

Appearance	NH100 Engine Specifications	
<p>NH150 engines are designed to fit a very wide range of applications. Two PTO shaft heights are available to ensure that you can find an engine to fit your machine. PTO heights are 99mm or 106mm. A wide range of PTO shafts are available including 3/4 inch.</p> 	Displacement (cc)	132
	Bore × stroke (mm)	61x45
	Oil quantity (cc)	500
	Recommended oil	10W-30
	Fuel tank volume (cc)	1200
	Starting System	Recoil
	Ambient temperature (°C)	5-40
	Operation counts	≤3
	Idle speed (r/min)	1400
	Start idle (r/min)	1440
	Idle speed control	Spring
	Rated power (kW/rpm)	2.2/3600
	Speed control power(kW/r)	2.2/3300
	Max torque (Nm/rpm)	6.5/2600
	Fuel type	92#
	Net weight (kg)	9.9
	Certification	EPA
	Endurance time (h)	500
	Filter configuration	FOAM
	Adjust Speed type	Manual mechanical adjustment
	Choke control	Manual
	Exhaust direction	Side
	Pulling direction	12 o'clock
	Fuel switch	Y
	Flameout method	Manual Flameout Switch
	Oil alarm	Y
	PTO	14#
	Component special status confirmation	Y
	Application (s)	General Purpose
Terminal main parameters		
Water pressure(psi)		
Effluent flow (GPM)		
Working speed (r/min)		
Idle speed		
start at idle speed		

Machine and side cover installation size

The figure contains two technical drawings of a machine. The left drawing is a front view showing a width of 162 and a height of 241. It also indicates a PTO shaft height of 96 and a mounting bracket height of 117.5. The right drawing is a side view showing a total width of 333 and a total height of 330. It details various mounting points with dimensions such as 88, 67, 32.55, and 4 x M8. A note specifies 'PTO Shaft Height 99mm and 106mm available.'

PTO Shaft Height 99mm and 106mm available.

包装信息:	

备注（客户其他特殊要求）:

- 1、
- 2、
- 3、