




**宗申动力**  
ZONG SHEN POWER

<b>WG15 1.5" Transfer Pump</b>	
<b>BOM No</b>	
<b>WG15</b>	
<b>NH150</b>	

<b>Appearance</b>	<b>WG15 1.5" Transfer Pump</b>	
	<b>Pump Type</b>	<b>Centrifugal Open Impeller</b>
	<b>Inlet Diameter (mm/inches)</b>	<b>40/2</b>
	<b>Outlet Diameter (mm/Inches)</b>	<b>40/2</b>
	<b>Max Head (m)</b>	<b>25</b>
	<b>Max Suction Head (m)</b>	<b>5</b>
	<b>Max Flow (l/hr)</b>	<b>10,000</b>
	<b>Net Weight (kg)</b>	<b>14</b>
	<b>Packing Size (cm)</b>	<b>44x37x42</b>
	<b>Sealing Material</b>	<b>VITON</b>
	<b>Engine</b>	
<b>NH150</b>		
<b>Displacement (cc)</b>	<b>149</b>	
<b>Bore × stroke (mm)</b>	<b>64x45</b>	
<b>Oil quantity (cc)</b>	<b>500</b>	
<b>Recommended oil</b>	<b>10w-30</b>	
<b>Fuel tank volume (cc)</b>	<b>1200</b>	
<b>Starting System</b>	<b>Recoil</b>	
<b>Ambient temperature (°C)</b>	<b>5-40</b>	
<b>Rated power (kW/rpm)</b>	<b>2.5/3600</b>	
<b>Max torque (N · m/rpm)</b>	<b>7.2/2600</b>	
<b>Fuel type (octane RON)</b>	<b>91</b>	
<b>Certification</b>	<b>EPA</b>	
<b>Endurance Validation (h)</b>	<b>500</b>	
<b>Filter configuration</b>	<b>Foam</b>	
<b>Choke control</b>	<b>Manual</b>	
<b>Flameout method</b>	<b>Manual Stop Switch</b>	
<b>Oil alarm</b>	<b>Y</b>	