



宗申动力
ZONG SHEN POWER

GB340-E	
BOM No	
GB340-E 11hp Engine	
(Electric Start)	

Appearance	GB340-E Engine Specifications	
	Displacement (cc)	337
	Bore × stroke (mm)	82 x 64
	Oil quantity (cc)	1100
	Recommended oil	10W-30
	Fuel tank volume (cc)	7500
	Starting System	Electric/Recoil
	Ambient temperature (°C)	-10~40
	Operation counts	≤3
	Idle speed (r/min)	1650±150
	Idle speed control	Spring
	Rated power (kW/rpm)	7.2/3600
	Max Torque Speed (N.m)	3800
	Specific Fuel Consumption Rate @ Rated Power (g/kW.h)	≤374
	Max torque (N • m/rpm)	21/2600
	Fuel type	92#
	Net weight (kg)	31.5
	Certification	EC(V)
	Endurance time (h)	500
	Filter configuration	PAPER+FOAM
	Adjust Speed type	Manual machinery control
	Choke control	MANUAL CHOKE
	Exhaust direction	SIDE
	Pulling direction	12'clock
	Fuel switch	Y
	Flameout method	Manual flameout switch
	Oil alarm	Y
	PTO (inch)	1"
	Component special status confirmation	Y
Application	General purpose	
Engine Dimension (cm)	48 x 42.5 x 50.5	